

VX PolyMaster Adhesive

VX PolyMaster Adhesive is a polymer modified, ready-to-use dry set adhesive composed of graded sand, cement and proprietary chemicals, which promotes good adhesion of non-absorptive tiles to suitable surfaces, to wall & floor, dry or wet interior or exterior areas including swimming pool.

ADVANTAGES

- Single component ready to use
- Excellent water & impact resistance
- Excellent adhesion to the substrates
- Adhere directly onto concrete block or brick, cement render
- Non-toxic
- Interior and exterior wall and floor
- User friendly / Easy installation
- Non-flammable

AREA OF APPLICATION

- Bathrooms
- Toilets or showers
- Swimming Pool
- Kitchens
- Fountains and lagoons

LIMITATION

PolyMaster Adhesive must not be used over wood, asphalt sheeting, masonite, glass or plastics and other unsuitable surfaces.

APPLICATION

- Ensure the surface is clean and free from curing compound.
- No chipping of the surface is required if the condition is stable.
- Any contamination including commercial detergents used for cleaning must be rinsed off with water.
- It should be ensured that substrate is free of all contaminants that could impair bonding.
- Scratch a small amount of material onto substrate to ensure proper bond, then addition material with a suitable trowel.
- Apply PolyMaster Adhesive to a uniform thickness to cover the keys on the substrate back to ensure full adhesive contact.
- The freshly applied PolyMaster Adhesive shall be protected from direct rain, dirt, oil, grease or other loose particle for at least 12 hours. It is foot trafficable after 24 hours.

MIXING

No mixing required.

PACKAGING

Available in 4 Litre pail.

STORAGE AND SHELF LIFE

Unopened PolyMaster Adhesive has a shelf life of 12 months if kept in dry storage condition.

HEALTH & SAFETY

To avoid PolyMaster Adhesive come into contact with skin & eyes or be swallowed, gloves & goggle are recommended when handling PolyMaster Adhesive. If eyes or skin contacted with the powder, wash thoroughly with clean water. If irritation persists, seek medical attention immediately.

Disclaimer. The information and the recommendations relating to the application and end use of this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability of final function at the job site is assumed. In practice, the differences in materials substrates and actual size conditions are such that no warranty in respect of merchantability of or fitness for particular purpose, nor any liability by the Company will be accepted for misuse, misreading or derivation from recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and all risks and liability in connection therewith. The information contained in the brochure may change at any time without notice.



