



VX WB Primer is a single component polymer modified high performance multi-purpose coating use as a waterproofing layer or as a priming layer for self-adhering membrane onto concrete substrate.

VX WB Primer provides quick drying for fast application and deliver excellent adhesion onto concrete substrate.

## PROPERTIES

<b>Colour</b>	Black / Brown
<b>Packaging</b>	20 KG
<b>Solid Content</b>	~ 60%
<b>Drying time</b> (30-degree ambient temperature)	2-3 hours
<b>Elongation</b>	~ 600%
<b>Heat Resistance</b>	~ 110°C

## RECOMMENDED COVERAGE

- When use as a priming layer: 0.20mm per 0.4kg/m<sup>2</sup>
- When use as a waterproof layer: 0.50mm per 1.0kg/m<sup>2</sup>

## STORAGE LIFE & SAFETY

- The material must be stored in original and unopened packaging and stored in cool and dry place.
- This product does not contain solvent.
- Do not inhale, swallow, avoid contact with eyes and skin.
- Refer to safety data sheet when in doubt.

## APPLICATION

- The substrate should be solid, firm and free from laitance, dust and dirt. All loose concrete shall be removed. VX WB Primer may be use on damp surface.
- VX WB Primer can be applied by roller, brush or spray applied directly to concrete substrate without dilution. For very porous substrate, it may be necessary to prime twice.
- Proceed to lay protective layer or lay self-adhering membrane once VX WB Primer turns touch dry.